

Sub  
D1

1. (Currently Amended): A door closer that holds a door at a fully closed position by engaging with a prescribed engagement member, wherein, when the engagement member is disengaged from the door closer, the door moves to a released position that is located slightly separate from the fully closed position in a door opening direction, the door closer comprising:

- a latch, which engages with the engagement member, wherein the latch rotates between an initial position at which the latch receives the engagement member and a fully latched position, and wherein, when the latch rotates from the initial position to the fully latched position after receiving the engagement member, the door is moved to the fully closed position;
- an urging member, which urges the latch toward the initial position;
- a ratchet, which is urged toward the latch, wherein, when the latch reaches the fully latched position, the ratchet engages with the latch to hold the latch at the fully latched position;
- an actuation mechanism, which separates the ratchet from the latch to disengage the ratchet from the latch, wherein, when the ratchet disengages from the latch, the urging member returns the latch from the fully latched position to the initial position such that the engagement member disengages from the latch and the door moves from the fully closed position to the released position;
- a courtesy switch, which detects that the door is located at a predetermined position separate from the released position in the door opening direction, wherein the actuation mechanism holds the ratchet at a position at which the ratchet cannot engage with the latch after the ratchet disengages from the latch, unless the ~~detection device~~ courtesy switch detects that the door is located at the predetermined position;
- a motor, which drives the actuation mechanism; and
- a controller, which controls the motor, said controller containing a timer having a settable reference time for latching operations, which when exceeded causes said motor to run in an inverse direction to reverse the latching operation.

2. (Cancelled)

3. (Currently Amended): The door closer as set forth in Claim 1, wherein the controller maintains the motor in a stopped state after the ratchet disengages from the latch,

unless the ~~detection device~~ courtesy switch detects that the door is located at the predetermined position.

4. (Previously Amended): The door closer as set forth in Claim 1, wherein the controller controls the motor such that the actuation mechanism disengages the ratchet from the latch in accordance with an external instruction.

5. (Original): The door closer as set forth in claim 1, wherein:  
the latch rotates from the initial position to the fully latched position via a latching start position;  
the ratchet is a first ratchet;  
the door closer further includes a second ratchet, which is urged toward the latch, wherein the second ratchet engages with the latch when the latch reaches the latching start position from the initial position; and  
the actuation mechanism moves the second ratchet such that the second ratchet rotates the latch to the fully latched position when the second ratchet engages with the latch.

6. (Previously Amended): The door closer as set forth in Claim 1, wherein:  
the latch rotates from the initial position to the fully latched position via a latching start position;  
the ratchet is a first ratchet;  
the door closer further includes a second ratchet, which is urged toward the latch, wherein the second ratchet engages with the latch when the latch reaches the latching start position from the initial position; and  
the controller instructs the actuation mechanism to move the second ratchet such that the second ratchet rotates the latch to the fully latched position when the second ratchet engages with the latch.

7. (Original): The door closer as set forth in claim 6, wherein the controller controls the motor such that the actuation mechanism disengages the second ratchet from the latch in accordance with an external instruction.

8. (Previously Amended): The door closer as set forth in Claim 1, wherein the actuation mechanism includes a rotary body driven by the motor and a rotational position sensor that detects a rotational position of the rotary body, and the controller controls the motor in accordance with the rotational position of the rotary body detected by the rotational position sensor.

9. (Original): The door closer as set forth in claim 8, wherein the rotational position sensor includes a conductor that is located on the rotary body to form a predetermined conductive pattern on the rotary body and a plurality of contact elements that contact the conductive pattern, and the controller determines the rotational position of the rotary body in accordance with signals from the contact elements.

10. (Currently Amended): The door closer as set forth in claim 1, wherein the ~~detection device~~ courtesy switch is a contact type switch.

c/ 11. (Currently Amended): A door closer that holds a door at a fully closed position by engaging with a prescribed engagement member, wherein, when the engagement member is disengaged from the door closer, the door moves to a released position that is located slightly separate from the fully closed position in a door opening direction, the door closer comprising:

- a latch, which engages with the engagement member, wherein the latch rotates between an initial position at which the latch receives the engagement member and a fully latched position, and wherein, when the latch rotates from the initial position to the fully latched position after receiving the engagement member, the door is moved to the fully closed position;
- an urging member, which urges the latch toward the initial position;
- a ratchet, which is urged toward the latch, wherein, when the latch reaches the fully latched position, the ratchet engages with the latch to hold the latch at the fully latched position;
- an actuation mechanism, which separates the ratchet from the latch to disengage the ratchet from the latch, wherein, when the ratchet disengages from the latch, the urging member returns the latch from the fully latched position to the initial position such that the engagement member disengages from the latch and the door moves from the fully closed position to the released position;

a motor, which drives the actuation mechanism;  
a controller, which controls the motor, said controller containing a timer having a settable reference time for latching operations, which when exceeded causes said motor to run in an inverse direction to reverse the latching operation; and  
a courtesy switch, which detects that the door is located at a predetermined position separate from the released position in the door opening direction, wherein the controller maintains the motor in a stopped state such that the actuation mechanism holds the ratchet at a position at which the ratchet cannot engage with the latch after the ratchet disengages from the latch, unless the ~~detection device~~ courtesy switch detects that the door is located at the predetermined position.

C) 12. (Original): The door closer as set forth in claim 11, wherein the controller controls the motor such that the actuation mechanism disengages the ratchet from the latch in accordance with an external instruction.

13. (Original): The door closer as set forth in claim 11, wherein the actuation mechanism includes a rotary body driven by the motor and a rotational position sensor that detects a rotational position of the rotary body, and the controller controls the motor in accordance with the rotational position of the rotary body detected by the rotational position sensor.

14. (Original): The door closer as set forth in claim 13, wherein the rotational position sensor includes a conductor that is located on the rotary body to form a predetermined conductive pattern on the rotary body and a plurality of contact elements that contact the conductive pattern, and the controller determines the rotational position of the rotary body in accordance with signals from the contact elements.

15. (Currently Amended): The door closer as set forth in claim 11, wherein the ~~detection device~~ courtesy switch is a contact type switch.

16. (Currently Amended): A door closer that holds a door at a fully closed position by engaging with a prescribed engagement member, wherein, when the engagement member is disengaged from the door closer, the door moves to a released position that is located slightly separate from the fully closed position in a door opening direction, the door closer comprising:

- a latch, which engages with the engagement member, wherein the latch rotates between an initial position at which the latch receives the engagement member and a fully latched position, and wherein, when the latch rotates from the initial position to the fully latched position via a latching start position between the initial position and the fully latched position after receiving the engagement member, the door moves to the fully closed position;
- an urging member, which urges the latch toward the initial position;
- a latching ratchet, which is urged toward the latch, wherein, when the latch reaches the latching start position from the initial position, the latching ratchet engages with the latch to rotate the latch to the fully latched position;
- a holding ratchet, which is urged toward the latch, wherein, when the latch reaches the fully latched position, the holding ratchet engages with the latch to hold the latch at the fully latched position;
- an actuation mechanism, which separates the latching ratchet and the holding ratchet from the latch to disengage the ratchets from the latch, wherein, when the ratchets disengage from the latch, the urging member returns the latch from the fully latched position to the initial position such that the engagement member disengages from the latch and the door moves from the fully closed position to the released position;
- a motor, which drives the actuation mechanism;
- a controller, which controls the motor, said controller containing a timer having a settable reference time for latching operations, which when exceeded causes said motor to run in an inverse direction to reverse the latching operation; and
- a courtesy switch, which detects that the door is located at a predetermined position separate from the released position in the door opening direction, wherein the controller maintains the motor in a stopped state such that the actuation mechanism holds each ratchet at a position at which the ratchet cannot engage with the latch after the ratchets disengage from the

latch, unless the ~~detection device~~ courtesy switch detects that the door is located at the predetermined position.

17. (Previously Added): The door closer as set forth in Claim 1, further comprising a Positive Temperature Coefficient thermistor, which is a protective element.

18. (Previously Added): The door closer as set forth in Claim 11, further comprising a Positive Temperature Coefficient thermistor, which is a protective element.

19. (Previously Added): The door closer as set forth in Claim 16, further comprising a Positive Temperature Coefficient thermistor, which is a protective element.

20. (New): A door closer that holds a door at a fully closed position by engaging with a prescribed engagement member, wherein, when the engagement member is disengaged from the door closer, the door moves to a released position that is located slightly separate from the fully closed position in a door opening direction, the door closer comprising:

a latch, which engages with the engagement member, wherein the latch rotates between an initial position at which the latch receives the engagement member and a fully latched position, and wherein, when the latch rotates from the initial position to the fully latched position after receiving the engagement member, the door is moved to the fully closed position;

an urging member, which urges the latch toward the initial position;

a ratchet, which is urged toward the latch, wherein, when the latch reaches the fully latched position, the ratchet engages with the latch to hold the latch at the fully latched position;

an actuation mechanism, which separates the ratchet from the latch to disengage the ratchet from the latch, wherein, when the ratchet disengages from the latch, the urging member returns the latch from the fully latched position to the initial position such that the engagement member disengages from the latch and the door moves from the fully closed position to the released position; and

a courtesy switch, which detects that the door is located at a predetermined position separate from the released position in the door opening direction, wherein the actuation mechanism holds the ratchet at a position at which the ratchet cannot engage with the latch after

c) the ratchet disengages from the latch, unless the courtesy switch detects that the door is located at the predetermined position.

---